

EnviroDuct®

1399-SD/1899-HD



APPLICATIONS

- Air Conditioning
- Ambient Air Movement
- Dehumidification

FEATURES

- Expanded pitch allows compression to one-seventh of its total extended length
- Flame resistant in accordance with UL94VTM-O, California Fire Marshal, and NFPA701 Specifications
- Excellent UV stabilization and mold and mildew inhibitors for rigorous outdoor use

This product is not recommended for aircraft ground support applications.

EnviroDuct® is a registered trademark of ABC Industries, Inc.



ENVIRODUCT®

*PVC/Polyester Substrate with Steel Wire Helix,
Sewn Construction*

SPECIFICATIONS

Weight	1399-SD: 13 oz./yd. ² (441 g/m ²) 1899-HD: 18 oz./yd. ² (610 g/m ²)	
Temperature	-20° to 180° F (-29° to 82° C)	
	Pitch	Diameters
Standard Pitch	3" (7.5 cm) 4" (10 cm)	6" & 7" (150 & 200 mm) 8" (200 mm) or Larger
Expanded Pitch	7" (18 cm)	12" (300 mm) or Larger
Wire	Hard-Drawn Steel	
Inside Diameter	6" - 36" (150 - 900 mm)	
Length	15', 25' (4.5, 7.5 m)	
Color	Black, Blue, Desert Tan, Green, Olive Drab, Red, White, Yellow	
Optional Wearstrip	Heavy-Duty Extruded, or Light-Duty PVC Fabric	
Optional End Finishes	Belt Cuff, Soft Cuff, Wire Rope Coupling	

ABC INDUSTRIES, INC.

P.O. Box 77, Warsaw, IN 46581-0077

800.426.0921 Toll-Free

574.267.5166 Phone

574.267.2045 Fax

sales@abc-industries.net

www.abc-industries.net

