EnviroDuct®







PVC Polyester Substrate with Steel Wire Helix, Sewn Construction

APPLICATIONS

- Air Conditioning
- Ambient Air Movement
- Dehumidification
- Drying
- General Purpose Blower Hose

FEATURES

- High opacity finish material helps block the sun's radiant heat, making it a clear choice for warm weather climates
- Expanded pitch allows compression up to one-seventh of its total extended length
- Flame resistant in accordance with UL94VTM-O, California Fire Marshal, and NFPA701 Method 2 Specifications
- Excellent UV stabilization and mold and mildew inhibitors for rigorous outdoor use

SPECIFICATIONS

SPECIFICATIONS	
Weight	16 oz./yd.² (542 g/m²)
Temperature	-20° to 180° F (-29° to 82° C)
Standard Pitch	3" (7.5 cm) 6" & 7" (150 & 200 mm) Diameters 4" (10 cm) 8" (200 mm) & Larger Diameters
Expanded Pitch	12" & Larger (300 mm & Larger) = 7" (18 cm) Diameter
Wire	Hard-Drawn Steel
Inside Diameter	6" - 36" (150 - 900 mm)
Length	15', 25' (4.5, 7.5 m)
Color	White
Optional Wearstrip	Heavy-Duty Extruded PVC
Optional End Finishes	Belt Cuff, Soft Cuff, Wire Rope Coupling

This product is not recommended for aircraft ground support applications.

EnviroDuct[®] is a registered trademark of ABC Industries, Inc.







ABC INDUSTRIES, INC.

P.O. Box 77, Warsaw, IN 46581-0077 800.426.0921 Toll-Free 574.267.5166 Phone 574.267.2045 Fax sales@abc-industries.net www.abc-industries.net