

THU-SD

ThermoHose®



APPLICATIONS

- Conveying Applications
- Lawn & Garden Equipment
- Light, Medium, & Heavy Material Handling

FEATURES

- Durable abrasion resistance
- High tensile strength
- Superior flexibility at low temperatures
- Solvent-free, odor-free
- Not subject to common bond failure
- Resistant to oil and ozone



THERMOHOSE®

*Thermoplastic Urethane
with Steel Wire Helix, Heat-Sealed Construction*

SPECIFICATIONS

Thickness	25 mil	
Temperature	-65° to 280° F (-54° to 138° C)	
	Pitch	Diameter
Standard Pitch	½" (1.5 cm)	2" (50 mm)
	¾" (2 cm)	3" (100 mm)
	1" (2.5 cm)	4"-30" (100 - 750 mm)
Wire	Hard-Drawn Steel	
Inside Diameter	2" - 30" (50 - 750 mm)	
Length	25' (7.5 m) Custom lengths available upon request.	
Color	Black, Clear (FDA Grade), Translucent Blue	

ABC INDUSTRIES, INC.

P.O. Box 77, Warsaw, IN 46581-0077

800.426.0921 Toll-Free

574.267.5166 Phone

574.267.2045 Fax

sales@abc-industries.net

www.abc-industries.net



Registered to
ISO 9001