

# Ultra High Temperature



## APPLICATIONS

- Extreme temperature air ducting
- Portable heater ducting with high heat content

## FEATURES

- Constructed to withstand the effects of prolonged heat subjection
- Flame resistant in accordance with UL94VTM-O



# ENVIRODUCT®

*Iron-oxide Coated Fabric  
on Fiberglass Substrate  
with Steel Wire Helix, Sewn Construction*

## SPECIFICATIONS

Weight	24 oz./yd. <sup>2</sup> (814 g/m <sup>2</sup> )	
Temperature	-65° to 900° F (-54° to 482° C) Intermittent to 1500° F (816° C)	
	Pitch	Diameters
Standard Pitch	3" (7.5 cm) 4" (10 cm)	6" & 7" (150 & 200 mm) 8" - 36" (200 - 900 mm)
Wire	Hard-Drawn Steel	
Inside Diameter	6" - 36" (150 - 900 mm)	
Length	15', 25' (4.5, 7.5 m)	
Color	Deep Red	
Standard End Finish	Soft Cuff	

This product is not recommended for aircraft ground support applications.

EnviroDuct® is a registered trademark of ABC Industries, Inc.

## ABC INDUSTRIES, INC.

P.O. Box 77, Warsaw, IN 46581-0077

800.426.0921 Toll-Free

574.267.5166 Phone

574.267.2045 Fax

sales@abc-industries.net

www.abc-industries.net



Registered to  
ISO 9001