

# Bridgehose



## APPLICATIONS

- Dust Collection
- Medium & Heavy Material Handling
- Paint & Sandblasting Operations

## FEATURES

- Heavy-duty construction for demanding positive and negative pressure applications
- Flame resistant in accordance with UL94VTM-O, California Fire Marshal, and NFPA701 Method 2 Specifications
- Excellent UV stabilization and mold and mildew inhibitors for rigorous outdoor use



# THERMOHOSE®

*PVC/Polyester Fabric with Steel Wire Helix,  
Heat-Sealed Construction*

## SPECIFICATIONS

Weight	13 oz./yd. <sup>2</sup> (441 g/m <sup>2</sup> ) 18 oz./yd. <sup>2</sup> (610 g/m <sup>2</sup> )
Temperature	-20° to 180° F (-29° to 82° C)
Standard Pitch	1.5" (50 mm)
Wire	12 Gauge, Hard-Drawn Steel — 8", 10", 12" Diameters 10 Gauge, Hard-Drawn Steel — 14", 16", 18", 20", 24" Diameters
Inside Diameter	8" - 24" (200 - 600 mm)
Length	25' (7.5 m)
Color	Black
Standard End Finish	Plain
Optional Wearstrip	Heavy-Duty Fabric

## ABC INDUSTRIES, INC.

P.O. Box 77, Warsaw, IN 46581-0077

800.426.0921 Toll-Free

574.267.5166 Phone

574.267.2045 Fax

sales@abc-industries.net

www.abc-industries.net



Registered to  
ISO 9001

