

EnviroDuct®

1399-SD InsulSand™



APPLICATIONS

- Air Conditioning
- Ambient Air Movement
- Dehumidification
- Drying
- General Purpose Blower Hose

FEATURES

- Three-Ply, Insulated Ducting
- Flame resistant in accordance with UL94VTM-O, California Fire Marshal, and NFPA701 Specifications
- Excellent UV stabilization and mold and mildew inhibitors for rigorous outdoor use



ENVIRODUCT®

PVC Polyester Substrate with Spun-Bound Polyester Insulation, Steel Wire Helix, Sewn Construction

SPECIFICATIONS

Weight	1399-SD: 13 oz./yd. ² (441 g/m ²)
Temperature	-20° to 180° F (-29° to 82° C)
Standard Pitch	3" (7.5 cm) 6" & 7" (150 & 200 mm) Diameters 4" (10 cm) 8" & Larger (200 mm & Larger) Diameters
Expanded Pitch	12" & Larger (300 mm & Larger) = 7" (18 cm) Diameter
Wire	Hard-Drawn Steel
Inside Diameter	6" - 36" (150 - 900 mm)
Length	15', 25' (4.5, 7.5 m)
Color	White, Yellow
Optional Wearstrip	Heavy-Duty Extruded PVC
Optional End Finishes	Belt Cuff, Soft Cuff, Wire Rope Coupling

ABC INDUSTRIES, INC.

P.O. Box 77, Warsaw, IN 46581-0077
 800.426.0921 Toll-Free
 574.267.5166 Phone
 574.267.2045 Fax
 sales@abc-industries.net
 www.abc-industries.net

This product is not recommended for aircraft ground support applications.

EnviroDuct® is a registered trademark of ABC Industries, Inc.
 InsulSand™ is a trademark of ABC Industries, Inc.



Registered to ISO 9001

06/18