

Silver Silicone



APPLICATIONS

- Extreme high or low temperature control
- Portable heating with moderate to high heat content

FEATURES

- Maintains its structural integrity under temperature duress
- Superior performance at both high and low temperatures



ENVIRODUCT®

Silicone, Rubber-Coated Fiberglass Fabric with Steel Wire Helix, Sewn Construction

SPECIFICATIONS

Weight	17.5 oz./yd. ² (593 g/m ²)	
Temperature	-67° to 500° F (-55° to 260° C)	
Standard Pitch	Pitch	Diameters
	3" (7.5 cm) 4" (10 cm)	6" & 7" (150 & 200 mm) 8" - 36" (200 - 900 mm)
Expanded Pitch	6" (15 cm)	12" (300 cm) or Larger
Wire	Hard-Drawn Steel	
Inside Diameter	6" - 36" (150 - 900 mm) Larger diameters available upon request.	
Length	15', 25' (4.5, 7.5 m)	
Color	Silver Gray	
Optional Wearstrip	Call for Details	
Optional End Finishes	Belt Cuff, Wire Rope Coupling, Soft Cuff	

This product is not recommended for aircraft ground support applications.

EnviroDuct® is a registered trademark of ABC Industries, Inc.

ABC INDUSTRIES, INC.

P.O. Box 77, Warsaw, IN 46581-0077

800.426.0921 Toll-Free

574.267.5166 Phone

574.267.2045 Fax

sales@abc-industries.net

www.abc-industries.net

