

TH-1/TH-2

ThermoHose®



APPLICATIONS

- Ambient Air Movement
- Conveying Applications
- Dehumidification
- Dust Collection
- Fume Removal
- Lawn & Garden Equipment
- Light & Medium Material Handling
- Painting & Sandblasting

FEATURES

- Portable, flexible, compressible design
- Flame resistant in accordance with UL94VTM-O, California Fire Marshal, and NFPA701 Method 2 Specifications



THERMOHOSE®

*PVC/Polyester Substrate with Steel Wire Helix,
Heat-Sealed Construction*

SPECIFICATIONS

Weight	TH-1: 13 oz./yd. ² (441 g/m ²) TH-2: 18 oz./yd. ² (610 g/m ²)
Temperature	-20° to 180° F (-29° to 82° C)
Standard Pitch	1.5" (4 cm)
Wire	Hard-Drawn Steel
Inside Diameter	2" - 24" (50 - 600 mm)
Length	25' (7.5 m)
Color	Black
Optional Wearstrip	Standard-Duty Extruded PVC, or Light-Duty PVC Fabric

ABC INDUSTRIES, INC.

P.O. Box 77, Warsaw, IN 46581-0077

800.426.0921 Toll-Free

574.267.5166 Phone

574.267.2045 Fax

sales@abc-industries.net

www.abc-industries.net



Registered to
ISO 9001

