

# THE-SD

ThermoHose®



## APPLICATIONS

- Ambient Air Movement
- Extreme High/Low Temperatures
- Fume Removal

## FEATURES

- Versatile, all-purpose ducting
- Excellent chemical and abrasion resistance
- Low compression and tension set
- Withstands the effects of weathering, ultraviolet rays, and ozone
- Not subject to common bond failure
- Resistant to flex fatigue, oils, hydrocarbons, and aqueous-based fluids
- Flame resistant in accordance with UL94VTM-O



# THERMOHOSE®

*Fabric Reinforced Thermoplastic Elastomer with Steel Wire Helix, Heat-Sealed Construction*

## SPECIFICATIONS

Weight	15 oz./yd. <sup>2</sup> (509 g/m <sup>2</sup> )	
Temperature	-65° to 250° F (-54° to 121° C)	
	Pitch	Diameter
Standard Pitch	½" (1.5 cm)	2" (50 mm)
	¾" (2 cm)	2.5"-3" (50-100 mm)
	1" (2.5 cm)	3.5"-8" (100-200 mm)
	2" (5 cm)	10"-20" (250-500 mm)
Expanded Pitch	3" (7.5 cm)	24"-42" (600-1,050 mm)
Wire	Hard-Drawn Steel	
Inside Diameter	2" - 42" (50 - 1,050 mm)	
Length	25', 50' (7.5, 15 m) Custom lengths available upon request.	
Color	Black, Yellow	
Optional Wearstrip	Standard-Duty Extruded PVC	
Standard End Finish	Plain	
Optional End Finishes	Belt Cuff, Soft Cuff, Wire Rope Coupling	

## ABC INDUSTRIES, INC.

P.O. Box 77, Warsaw, IN 46581-0077

800.426.0921 Toll-Free

574.267.5166 Phone

574.267.2045 Fax

sales@abc-industries.net

www.abc-industries.net



Registered to  
ISO 9001