

ValuHeat

EnviroDuct®



APPLICATIONS

- Portable heater ducting with moderately high heat content
- Blowing

FEATURES

- Durable fabric composition prevents odor and smoke expulsion at high temperatures
- Tear-resistant fabric
- UV stabilized and mold/mildew inhibited for rigorous outdoor use
- Flame resistant in accordance with UL94VTM-O



ENVIRODUCT®

*Thermoplastic Elastomer
with Warp Knit Backer, Steel Wire Helix,
Sewn Construction*

SPECIFICATIONS	
Weight	11 oz./yd. ² (373 g/m ²)
Temperature	-65° to 350° F (-54° to 177° C) Intermittent
Standard Pitch	8" (200 mm)
Wire	Hard-Drawn Steel
Inside Diameter	12", 16" (300, 400 mm). Other diameters available upon request.
Length	Maximum 30' (9 m)
Color	Charcoal Gray
Optional Wearstrip	Call for Details
Optional End Finishes	Belt Cuff, Wire Rope Coupling, Screw Clamp Cuff, Pinlock Coupling, Soft Cuff

This product is not recommended for aircraft ground support applications.

EnviroDuct® is a registered trademark of ABC Industries, Inc.

ABC INDUSTRIES, INC.

P.O. Box 77, Warsaw, IN 46581-0077

800.426.0921 Toll-Free

574.267.5166 Phone

574.267.2045 Fax

sales@abc-industries.net

www.abc-industries.net

